



NOTES

General
Builder to provide all labour, materials,
fittings, plant, tools, permits, insurances
etc necessary for the proper completion of
the work and ensure that all labour and
materials in all trades are the best of

conditions and scope of work prior to commencing. All necessary allowances are to be included such as costs associated with demolition making good, matching existing detail, travelling costs and the like as required for the satisfactory completion of the alterations whether expressly indicated or not and as necessitated by site

Where adjustments are required to suite site conditions consult client for approval.

Materials and workmanship to be in accordance with the Building Code of Australia , the ACT. Appendix, and all other relevant codes.

DEMOLITION
Provide all necessary demolition work
required for the proper completion or the of
the renovations, alterations and all other associated works.

Where demolition work is carried out ensure that adequate structural support is provided to maintain the integrity of existing structure prior to removing any existing

Protect materials and property from damage.

Make good existing work that has been damaged. New detail to match existing where appropriate and, unless otherwise directed. new finish to blend into adjacent surfaces

ensure that all redundant services are made safe.

Standard To AS 2601. MATERIALS AND COMPONENTS Hazardous materials
Give notice immediately any
hazardous materials or conditions
are found.

Demolished materials
Except for materials as directed
by the client to be salvaged or reused, demolished materials are the
property of the contractor and must
be removed from the site. Do not burn or bury demolished materials on the site.

Salvage: Recover materials to be salvaged or re-used without damage

Re-use: Re-use only materials recovered from the demolitions in a sound and suitable condition.

Storage: Store in an approved location any materials to be re-

to prevent spillage.

Provide temporary support for sections of existing buildings which are to be altered and which normally rely for support on work to be demolished. Support until permanently supported on new work. Clear away temporary supports on

Ground support: Support excavations for demolition of underground structures.

Weather protection
If walls or roofs are opened for
alterations and additions or the
surfaces of adjoining buildings are
exposed, provide temporary covers
to prevent water penetration. Provide covers to protect existing plant and equipment and material

Weather protection If walls or roofs are opened for alterations and additions or the surfaces of adjoining buildings are exposed, provide temporary covers to prevent water penetration. Provide covers to protect existing plant and equipment and material intended for re-use.

Dust protection
Provide dust-proof screens,
bulkheads and covers to protect existing finishes and the immediate environment from dust and debris.

Explosives
Do not use explosives.

Dust protection
Provide dust-proof screens, bulkheads and covers to protect existing finishes and the immediate environment from dust and debris.

Explosives Do not use explosives

OZTAL ARCHITECTS

DEAKIN ACT LEVEL 2 PACIFIC HIGHWAY ST LEONARDS NSW 2065 P- 02 9906 1922 F- 02 9439 0255 DRAWING TITLE **DEMOLITION PLAN** NOMINATED ARCHITECT: NICK PELLE NSW REGISTRATION NO: 5628 A DA ISSUE DK 8.10.20 BY DATE REV DESCRIPTION

PROJECT NAME BLOCK 28 SECTION 2 PROPOSED ALTERATIONS **COCHERE & STUDIO**

D & C MCINNES

SCALE

PRINT DATE 08.10.20 DESIGNED/ DM / DK DRAWN PROJECT No 001097

A004 REVISION A DWG No DRAWING STATUS WORKS APPROVAL

1:100